





Applicant: Leading Edge Novelty

Contact information: 33 North Mall Plainview, NY 11803

The following sample(s) was (were) submitted and identified by client as:

Sample Description : Toy car

Item No. : F123

Packaging Provided : Yes

Labeled Age Grading : 3+

Requested Age Grading : 3+

Age Group Applied in Testing : 3+

Received Date : Mar. 15, 2023

Testing Period : From Mar. 15, 2023 to Mar. 21, 2023

Test Request : Please refer to next page(s).

Test Result(s) : Please refer to next page(s).

Shen Zhen UONE Test Co., LTD.

Prepared by Checked by

Thea Ye Marcia Deng Lewis Liu

Varcia

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Approved by



Report No.: U01103230315116-1E Query Password: QW3301 Date: Mar. 21, 2023 Page 2 of 15

	$T_{\mu\nu}^{-}$ $^$	2011011101011
IES	T REQUEST	CONCLUSION
AST	M F963-17 American Standard Consumer Safety Specification for Toy Safety	
(1)	Mechanical and Physical Properties	PASS
(2)	Flammability	PASS
(3)	Battery-Operated Toys for Section 4.25	PASS
(4)	Total Lead content in paint and surface coating	PASS
(5)	Total Lead content in substrate material	PASS
(6)	Soluble Heavy Metals content in paint and surface coating	PASS
(7)	Soluble Heavy Metals content in substrate material	PASS
U.S.	Consumer Product Safety Improvement Act of 2008(CPSIA) Section 103	
(8)	Tracking labels for children's products	PASS



Test Material(s) List

Material No.	Description (Location)	Remark
101 10	Black plastic	101 101
2	White plastic	1
3	Red plastic	OHE OHE
4	Silvery coating	1 0
5	Grey soft plastic	SE SE

### Test Result(s):

(1) Mechanical and Physical Properties - ASTM F963-17

Section	Test Item	Assessment
4.1	Material Quality	PASS
4.3.7	Stuffing Materials	NA
4.4	Electrical/Thermal Energy*	NA
4.5	Sound-Producing Toys	PASS
4.6	Small Objects	NA
4.6.1	Toys that are intended for children under 36 months of age	NA
4.6.2	Mouth-Actuated Toys*	NA
4.6.3	Toys and games that are intended for use by children who are at least three years old but less than six years of age	NA
4.7	Accessible Edges	PASS
4.8	Projections	PASS
4.9	Accessible Points	PASS
4.10	Wires or Rods	NA
4.11	Nails and Fasteners	PASS
4.12	Plastic film	PASS
4.13	Folding Mechanisms and Hinges	NA
4.14	Cords ,straps, and Elastics	NA
4.15	Stability and Over-Load Requirements*	NA

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

深圳市宇冠检测有限公司 Shen Zhen UONE Test Co., LTD. Hotline:400-774-3358 Web:www.uonetest.com Tel:+86-755-23695858 Web:www.uonecn.com Fax:+86-755-23699878 E-mail:service@uonetest.com



Section	Test Item	Assessment
4.16	Confined Spaces	NA
4.17	Wheels, Tires and Axles <36M	PASS
4.18	Holes, Clearance, and Accessibility of Mechanisms	PASS
4.19	Simulated Protective Devices	NA O
4.20	Pacifiers	NA
4.21	Projectiles Toys	NA O
4.22	Teethers and Teething Toys	NA
4.23	Rattles	NA
4.24	Squeeze Toys	NA
4.26	Toys Intended to be Attached to a Crib or Playpen	NA
4.27	Stuffed and Beanbag-Type Toys	NA NA
4.28	Stroller and Carriage Toys	NA
4.29	Art Materials*	NA O
4.30	Toy Gun Marking*	NA
4.31	Balloons	NA O
4.32	Certain Toys with Spherical Ends	NA
4.33	Marbles	NA
4.34	Balls	NA
4.35	Pompoms	NA
4.36	Hemispheric-Shaped Objects	NA NA
4.37	Yo Yo elastic tether toys*	NA
4.38	Magnets	NA S
4.39	Jaw Entrapment in Handles and Steering Wheels	NA
4.40	Expanding Materials	NA
4.41	Toy Chests	NA
5	Safety Labeling Requirements	OHE OHE O
5.1	Federal Government Requirements	PASS



Section	Test Item	Assessment
5.2	Age Grading Labeling	PASS
5.3	Safety Labeling Requirements	NA NA
5.4	Aquatic Toys	NA
5.5	Crib and Playpen Toys	NA
5.5.1	Age Grading	NA
5.5.2	Safety Labeling	NA
5.6	Mobiles	NA
5.7	Stroller and Carriage Toys	NA
5.8	Toys Intended to be Assembled by an Adult	NA
5.9	Simulated Protective Devices	NA
5.10	Toys with Functional Sharp Edges and Sharp Points (4-8yrs)	NA NA
5.11	Small Objects, Small Balls, Marbles, and Balloons	NA
5.12	Toy Caps	NA
5.13	Art Materials	NA
5.14	Electric Toys	NA
5.16	Promotional Materials	PASS
5.17	Magnets	NA
6	Instructional literature	20 20
6.1	Definition and Description	PASS
6.2	Crib and Playpen Toys	NA
6.3	Mobiles	NA
6.4	Toys Intended to be Assembled by an Adult	NA
6.7	Toys in Contact with Food	NA
6.8	Toy Chests	NA
7	Producer's Markings	
7.1	Producer's Markings	PASS
7.3	Toy Chests	NA



Query Password: QW3301 Report No.: U01103230315116-1E Date: Mar. 21, 2023 Page 6 of 15

Section	Test Item	Assessment
8.5	Normal Use Testing	PASS
8.5.1	Washable Test	NA
8.7	Impact Test	PASS
8.8	Torque Test	PASS
3.9	Tension Test	PASS
3.10	Compression Test	NA
3.11	Test for Tire Removal and snap-in wheel and axle assembly removal	PASS
3.12	Flexure Test	NA
3.13	Test for Mouth-Actuated Toys and Mouth-Actuated Projectile Toys*	NA
3.14	Projectiles	NA
3.15	Test for Stability of Ride-on Toys or Toy Seats*	NA
3.16	Tension Test for Pompoms	NA
3.20	Tests for Toys Which Produce Noise	PASS
3.21	Dynamic Strength Test for Wheeled Ride-on Toys*	NA
3.22	Plastic Film Thickness	PASS
3.23	Test for Loops and Cords	NA
3.24	Yoyo Elastic Tether Toy Test Methods*	NA
3.25	Magnet Test Methods	NA
3.26	Test Methods for Locking Mechanisms or Other Means*	NA
3.27	Test for Toy Chest Lids and Closures*	NA
8.28	Test for Overload of Ride-on Toys and Toy Seats	NA
3.29	Stuffing Materials Evaluation	NA NA
3.30	Expanding Materials Test Method	NA

NA = Not applicable Remark:

"\*"= The Test Item(s) was(were) not got CNAS accreditation.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

深圳市宇冠检测有限公司 Shen Zhen UONE Test Co., LTD. Hotline:400-774-3358 Web:www.uonetest.com Tel:+86-755-23695858 Web:www.uonecn.com Fax:+86-755-23699878



(2) Flammability - ASTM F963-17 Section 4.2

Section	Test Item	Assessment
4.2	Flammability	PASS See Note

Note: Flammability of Solids and Soft Toys - ASTM F963-17(A5)

Sample	Burn Rate (in./sec.)	Limit (in./sec.)	
Toy	0.02	0.1	

Remark:

 All styles of submitted sample(s) (and its accessories) was/were tested, the above result only showed the most severe burn rate.

### (3) Battery-Operated Toys - ASTM F963-17 Section 4.25

Power Source: Car: 1 x 3.7 V, 1200mAh replaceable rechargeable battery

Controller: 2 x 1.5 V, AA replaceable

Section	Test Item	Assessment
4.25	Battery-operated toys	PASS
4.25.1	Battery information marking in battery compartment	PASS
4.25.1.1	Label for non-replaceable batteries	NA
4.25.2	Nominal voltage between any two accessible points not exceed 24 V	PASS
4.25.3	Designed to prevent charge any non-rechargeable battery	NA
4.25.4	Toys intended for children less than 3 years old,all batteries not be accessed before or after foreseeable abuse testing	NA
4.25.5	Small batteries not be accessed before or after foreseeable abuse testing	NA
4.25.6	Isolation of batteries of different type or capacities	PASS
4.25.7	Temperature on battery surface not exceeding 71 ℃	PASS
4.25.7.1	Battery operated toys during normal use conditions	PASS
4.25.7.2	Lock external moving parts of toy	PASS
4.25.8	No condition occurred that cause battery overheat or present a combustion hazard	PASS

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

深圳市宇冠检测有限公司 Shen Zhen UONE Test Co., LTD.



Section	Test Item	Assessment
4.25.8.1	Temperature on rechargeable lithium batteries during normal use charging and any discharging of the battery	PASS
4.25.9	Instruction requirement	PASS
4.25.10*	Battery-powered ride on toys	NA
4.25.11*	Toys that Contain Secondary Cells or Secondary Batteries	PASS
4.25.11.1*	lithium ion or lithium ion polymer cells comply with standard ANSI C18.2M Part 2 or UL 1642 or IEC 62133	PASS
4.25.11.2*	Lithium ion or lithium ion polymer batteries comply with standard ANSI C18.2M Part 2 or UL 2054 or IEC 62133	PASS
4.25.11.3*	Lithium ion or lithium ion polymer cells provided with an enclosure that provides protection against damage to the cells and their circuitry during normal use and foreseeable abuse of the toy	PASS
4.25.11.4*	During charging with the provided charging device, no cell shall exceed the cell or battery manufacturer's specified charging voltage, current, and temperature values	PASS
1.25.11.5*	During discharge with the provided charger and load, Any cell's maximum discharge current shall not exceed the cell manufacturer's specifications during normal operation and stalled motor test	PASS
	Lithium ion or lithium ion polymer cell(s) cutoff voltage shall not be less than the manufacturer's specified minimum in any operating mode.	PASS
1.25.11.6*	During normal use charging and discharging, Temperature rises on any battery surfaces or any other accessible surface of the toy exceeding:25°C(metal surface) or 30°C(ceramic/ glass surface) or 35°C(wood/ plastic surface)	PASS
1.25.11.7*	Plug into the electric mains power battery chargers or power adaptors shall be listed by a Nationally Recognized Test Laboratory (NRTL)	NA
	During charging external connectors shall ensure correct polarity	NA



Section	Test Item	Assessment
4.25.11.8*	Circuit wiring connected to lithium ion or lithium ion polymer and NiMH secondary batteries shall be short circuit protected Not present the risk of fire when tested in accordance with 8.19.5 Temperatures on any accessible surfaces of any secondary battery shall not exceed the limit Cells shall not cause battery explosion.burning or charring of the combustible materials If cells vent, electrolyte shall not become accessible Removable secondary batteries was not able to be short circuited by placing terminals of opposite polarity against a flat conductive surface Short circuit protection shall be incorporated into lithium ion or lithium ion polymer batteries.	PASS
5.15	No-replaceable batteries	NA
5.15.1	Instruction for Battery-powered ride on toys	NA
5.15.2	Instruction for button or coin cell batteries	NA
6.5	Instruction on safe battery usage	PASS
6.6	Battery Powered Ride-on Toys	NA
7.2	Battery-Powered Ride-on Toys	NA
8.17	Stalled Motor Test for Battery-operated Toys	PASS
8.19*	Tests for Toys that Contain Secondary Cells or Batteries	PASS
8.19.1*	Pre-Conditioning	PASS
8.19.2*	Battery Overcharge Test	NA NA
8.19.3*	Repetitive Overcharge Test	PASS
8.19.4*	Single Fault Charging Test	PASS
8.19.5*	Short Circuit Protection Test	PASS
8.19.5.1*	Removable Batteries	PASS
8.19.5.2*	Toys Using Lithium Batteries	PASS
8.19.5.3*	Toys Using Nickel Metal Hydride Batteries	NA

**Remark:** NA = Not Applicable.

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

深圳市宇冠检测有限公司 Shen Zhen UONE Test Co., LTD. Hotline:400-774-3358 Web:www.uonetest.com Tel:+86-755-23695858 Web:www.uonecn.com Fax:+86-755-23699878 E-mail:service@uonetest.com



"\*"= The Test Item(s) was(were) not got CNAS accreditation

Test Item	Result	
Maximum Charge voltage(V)	4.14	1019
Maximum Charge current(mA)	600	
Maximum discharge current (mA)	2790	.019
Charge cutoff voltage(V)	4.47	0
Discharge cutoff voltage(V)	3.04	-13

Clause 4.25.7 Temperature on battery surface						
HOLE HOLE HOLE HOLE	Maximum temp	Limited				
Location	Normal Use	stalled motor	(℃)			
Ambient temperature	23.3	23.2	0,-140,			
Battery surface (Car:Battery box)	34.6	34.6	71			
Battery surface (R/C)	25.3	is all all	71			

Clause 4.25.8.1 & 4.25.11.4 Temperature test						
OHE OHE SOME SOME SO	Maximum temperature(℃)					
Condition	Battery surface	Ambient temperature  23.2  23.3  23.4	(℃)			
Normal Charge	27.3	23.2	60			
Normal Discharge	33.7	23.3	60			
Clasuse 8.19.1 Pre-Conditioning	27.5	23.4	1			
Clasuse 8.19.3 Repetitive Overcharge Test	28.2	23.8				



Clause 4.25.11.6 Temperature rise test							
Condition	all all	Maximum temperature rise ( $^{\circ}\!$					
Condition	0, 10,	Battery surface	Battery surface Ambient temperature				
Clasuse 8.19.1	Charge	3.7	23.3	35			
Pre-Conditioning	Discharge	11.3	23.1	35			
Clasuse 8.19.3 Repetitive Overcharge Test	Charge	4.5	23.3	35			

Clasuse 8.19.5 Short Circuit Protection Test						
Location	Accessible	Maximum temperature(℃):	Ambient temperature(℃):	Limited(°C)		
Battery surface	Yes	25.3	23.3	60		



#### (4) Total Lead content in paint and surface coating - ASTM F963-17 Section 4.3.5.1

<u>Test Method:</u> With reference to ASTM F963-17 Section 8.3.1, was analyzed by Atomic Absorption Spectrometer (AAS) or Inductively Coupled Plasma Optical Emission Spectrometer (ICP-OES).

Material No.	Material No. MDL (mg/kg)		Result (mg/kg) Conclusi		
4	10	90	N.D.	PASS	

Note:

- 1. mg/kg = milligram per kilogram (ppm).
- 2. N.D. = Not Detected (< MDL).
- 3. MDL = method detection limit.

### (5) Total Lead content in substrate material - ASTM F963-17 Section 4.3.5.2

<u>Test Method:</u> With reference to ASTM F963-17 Section 8.3.1, was analyzed by Atomic Absorption Spectrometer (AAS) or Inductively Coupled Plasma Optical Emission Spectrometer (ICP-OES).

Material No.	MDL (mg/kg)	Limit (mg/kg)	Result (mg/kg)	Conclusion	
ME 1 ME	10	100	N.D.	PASS	
2 110	10	100	N.D.	PASS	
3	10	100	N.D.	PASS	
1012 2 1012	10	100	N.D.	PASS	

Note

- mg/kg = milligram per kilogram (ppm).
- 2. N.D. = Not Detected (< MDL).
- 3. MDL = method detection limit.

### (6) Soluble Heavy Metals content in paint and surface coating - ASTM F963-17 Section 4.3.5.1

<u>Test Method:</u> With reference to ASTM F963-17 Section 8.3.2 to Section 8.3.5, was analyzed by Inductively Coupled Plasma Optical Emission Spectrometer (ICP-OES).

Elements	Sb	As	Ва	Cd	Cr	Pb	Hg	Se	N. N.	
Limit (mg/kg)	60	25	1000	75	60	90	60	500	Ola Pola	
MDL (mg/kg)	5	2.5	5	5	5	5	5	5	Conclusion	
Material No.	Material No. Result (mg/kg)									
4	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	PASS	

This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

深圳市宇冠检测有限公司 Shen Zhen UONE Test Co., LTD.



Report No.: U01103230315116-1E Query Password: QW3301 Date: Mar. 21, 2023 Page 13 of 15

Note

- mg/kg = milligram per kilogram (ppm).
- 2. N.D. = Not Detected (< MDL).
- 3. MDL = method detection limit.
- 4. All the reported results of soluble heavy metals are adjusted analytical results with the analytical correction shown in the following table.

Element	Sb	As	Ва	Cd	Cr	Pb	Hg	Se
Analytical correction (%)	60	60	30	30	30	30	50	60

#### (7) Soluble Heavy Metals content in substrate material - ASTM F963-17 Section 4.3.5.2

<u>Test Method:</u> With reference to ASTM F963-17 Section 8.3.2 to Section 8.3.5, was analyzed by Inductively Coupled Plasma Optical Emission Spectrometer (ICP-OES).

Elements	Sb	As	Ва	Cd	Cr	Pb	Hg	Se	OHE OHE
Limit (mg/kg)	60	25	1000	75	60	90	60	500	
MDL (mg/kg)	5	2.5	5	5	5	5	5	5	Conclusion
Material No.	2. 10.								
	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	PASS
10,5 10,	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	PASS
3	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	PASS
5	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	N.D.	PASS

Note:

- 1. mg/kg = milligram per kilogram (ppm).
- 2. N.D. = Not Detected (< MDL).
- 3. MDL = method detection limit.
- 4. All the reported results of soluble heavy metals are adjusted analytical results with the analytical correction shown in the following table.

Element	Sb	As	Ва	Cd	Cr	Pb	Hg	Se
Analytical correction (%)	60	60	30	30	30	30	50	60



### (8) Tracking labels for children's products

Test Item	Test Method	Requirement	Result
10 10 10 10	a light light	A permanent and distinguishing mark on the product and its packaging,to the	10 lb 10 lb
Tracking labels for children's products	Consumer Product Safety Improvement Act of 2008	extent practicable,enabling the manufacturer and purchaser to ascertain the name of the manufacturer	Comply with the requirement
10HE 10HE 10T	E JOHE JOHE	or private labeler,location and date of production of the product.	

### Photo(s) of Sample:





\*\*\*End of Report\*\*\*



#### Statement

- The information as listed on the first page of this test report was all provided by the client except the
  received date, testing period, test result(s) and test request. The client shall be responsible for the
  representativeness of sample and authenticity of materials, for which UONE shall bear no
  responsibilities.
- Unless otherwise stated the results shown in this report refer only the sample(s) tested and does not bear other joint and several liabilities.
- This report is considered invalidated without the Special Seal for Inspection of the UONE, This report shall not be altered, increased or deleted.
- Without written approval of UONE, this report shall not be reproduced in part or published as advertisement.
- 5. Objection should be issued in 15 days upon receiving the report, overdue opinion is inadmissible.
- If the report is not stamped with the accreditation recognized seal, it will only be used for scientific research, education, and internal quality control activities, and is not used for the purpose of issuing supporting data to the society.